



TECHNICAL SPECIFICATION

Technical Service Department,
JSP Ltd., Worsham Mill, Minster
Lovell, Oxford, OX29 0TA
Tel.: 01993 824000
Fax: 01993 824422

Mkl / Contractahat Industrial Safety Helmet

Conformity:

Conforms to BS EN 397.
EC Certificate Number 0279, issued by
BSi Product Certification.

- Low dome profile
- Helmet offers electrical insulation
- Available in a choice of colours
- Incorporates a rain channel
- Company personalisation available by printing
- Compatible with other JSP safety products.

Size & Weights:

530 – 620mm (6½ - 7⅞) 0.34Kg
(weight is appox.)

Materials:

Shell: HDPE
Poly Harness: LDPE
Brushed Nylon Backed Foam or
'Nomaz' Leatherette Sweatbands are
available



Instructions For Use:

Fit helmet on head and fasten strap to ensure correct fit. For adequate protection this helmet must be worn with the peak facing forward and be adjusted to the size of the users head.

Limitations Of Use:

Protection will only be offered if the helmet is fitted correctly. Any Helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer. The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice. The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.

Cleaning & Maintenance:

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.